



ENVIRONMENTAL HEALTH AND SAFETY
STANDARD OPERATING PROCEDURES

SOP No. 24.01.01.W1.27AR Personal Protective Equipment Procedure

Approved: August 15, 2010

Revised: October 19, 2018

Next Scheduled Review: October 19, 2023

Environmental Health and Safety at WTAMU is composed of two distinct but integrated environmental safety departments that report to the Vice President of Research and Compliance. Academic and Research Environmental Health and Safety (AR-EHS) is responsible for research and academic related compliance, which includes laboratory and academic research and the associated compliance committees. Fire and Life Safety (FLS-EHS) is responsible for fire related compliance and conducts fire and life safety inspections of campus buildings and assists with the testing all fire detection and suppression systems.

Supplements TAMUS Regulation 24.01.01

Contents

1. Purpose..... 1
2. Scope..... 2
3. Arm and Hand Protection..... 2
4. Body Protection 2
5. Ear and Hearing Protection..... 2
6. Eye and Face Protection 3
6.1. Eye Wash Stations..... 3
7. Foot Protection..... 4
8. Head Protection 4
9. Respiratory Protection..... 4
9.1. Usage Requirements..... 4
9.2. Types of Respirators..... 4
9.3. Selecting a Respirator..... 5
9.4. Using Respirators Safely..... 6
10. Showers 6
11. Training 6
12. Record Retention..... 7

1. Purpose

Personal Protective Equipment (PPE) includes all clothing and work accessories designed to protect employees from workplace hazards. Protective equipment should not replace engineering, administrative, or procedural controls for safety; it should be used in conjunction with these controls. Employees must wear protective equipment as required and when instructed by a supervisor.

IMPORTANT: Always remove protective clothing before leaving the work area. Do not wear PPE in public elevators, classrooms, restrooms, break-rooms, etc.

2. Scope

This procedure is designed to inform all WTAMU employees and staff of the proper use of personal protective equipment. All employees and staff should refer to this procedure when PPE are necessary.

3. Arm and Hand Protection

Arms and hands are vulnerable to cuts, burns, bruises, electrical shock, chemical spills, and amputation. The following forms of hand protection are available for employees.

- Disposable exam gloves
- Rubber gloves
- Nitrile gloves
- Neoprene gloves
- Leather gloves
- Non-asbestos heat-resistant gloves
- Metal-mesh gloves for meat cutters
- Cotton gloves

Always wear the appropriate hand and arm protection. Double your hand protection by wearing multiple gloves when necessary (e.g., two pairs of disposable gloves for work involving biological hazards). For arm protection, wear a long-sleeved shirt, a laboratory coat, chemical-resistant sleeves, or gauntlet-length gloves. Follow these guidelines to ensure arm and hand safety.

- Inspect and test new gloves for defects.
- Always wash your hands before and after using gloves. Wash chemical-protective gloves with soap and water before removing them.
- Do not wear gloves near moving machinery; the gloves may become caught.
- Do not wear gloves with metal parts near electrical equipment.

IMPORTANT: Gloves are easily contaminated. Avoid touching surfaces such as telephones, doorknobs, etc. when wearing gloves.

4. Body Protection

Hazards that threaten the torso tend to threaten the entire body. A variety of protective clothing, including laboratory coats, long pants, rubber aprons, coveralls, and disposable body suits are available for specific work conditions. Rubber, neoprene, and plastic clothing protect employees from most acids and chemical splashes. Laboratory coats, coveralls, and disposable body suits protect employees and everyday clothing from contamination, and welding aprons provide protection from sparks.

NOTE: Launder reusable protective clothing separate from other clothing.

5. Ear and Hearing Protection

If you work in a high noise area, wear hearing protection. Most hearing protection devices have an assigned rating that indicates the amount of protection provided. Depending on your level of exposure, you may choose from the following devices.

- Disposable earplugs
- Reusable earplugs
- Headband plugs
- Sealed earmuffs

Earplugs may be better in hot, humid, or confined work areas. They may also be better for those who wear other PPE, such as safety glasses or hats. Earmuffs, on the other hand, may be better for employees who move in and out of noisy

areas, because the muffs are easier to remove. Before resorting to hearing protection, attempt to control noise levels through engineering or operational changes. To avoid contamination, follow these guidelines when using earplugs.

- Wash your hands before inserting earplugs.
- Replace disposable earplugs after each use.
- Clean reusable earplugs after each use.
- Contact EHS for more information.

6. Eye and Face Protection

Employees must wear protection if hazards exist that could cause eye or face injury. Eye and face protection should be used in conjunction with equipment guards, engineering controls, and safe practices.

Always wear adequate eye and face protection when performing tasks such as grinding, buffing, welding, chipping, cutting, or pouring chemicals. Safety glasses with side shields provide protection against impact and small splashes, but safety goggles provide protection against impact, splashes, and some protection against hazardous atmospheres.

IMPORTANT: Do not wear contact lenses in the laboratory or other areas where hazardous atmospheres may be present. Contact lenses do not provide eye protection and may reduce the effectiveness of an emergency eyewash.

When using eye and face protection remember the following.

- If you wear prescription glasses, either wear corrective eye protection or wear goggles or other safety protection over the glasses.
- Safety glasses with side shields provide primary protection to eyes and are four times as resistant as prescription glasses to impact injuries.
- Goggles protect against impacts, sparks, chemical splashes, dust, and irritating mist. Wear full goggles, not just safety glasses, when working with chemicals.
- Eyecup welding goggles with filter lenses give protection from glare and sparks.
- A welding helmet protects from flash burn due to welding, soldering, or brazing, but does not provide primary eye protection; safety glasses or goggles should be worn with the helmet.
- A face shield is designed to protect the face from some splashes or projectiles but does not eliminate exposure to vapors. A face shield should be worn with goggles or safety glasses.
- Sunglasses are useful to prevent eyestrain from glare and to minimize ultraviolet light exposure.

6.1. Eye Wash Stations

Eye wash stations provide emergency eye treatment for people exposed to hazardous materials. There are three common types of eye wash stations.

Eye Wash Bowls - These stations are ANSI approved and are usually attached to emergency showers. They provide a continuous water flow and are recommended for laboratories and other locations with hazardous materials.

Drench Hoses at Sinks - These stations provide a continuous water flow, but they are easily contaminated with sediment, and they do not allow the free use of both hands; the use of both hands may be necessary. Drench hoses are ANSI approved, and they are preferred for laboratory usage. If you have a drench hose in your work area, flush the hose regularly to remove any sediment.

Plastic Eye Wash Bottles - These stations do not provide a continuous water flow, and they do not allow free use of both hands. They are not approved in laboratories or other hazardous areas. Plastic eye wash bottles are ideal, however, for portable eye wash needs and short-term operations where continuous flowing water is not immediately available. If you have a plastic eye wash bottle in your work area, make sure it is filled with sterile water or changed weekly.

IMPORTANT: If the eyes are exposed to hazardous materials or irritating elements, immediately flush the eyes with water for at least 15 minutes. Contact a physician, if necessary.

7. Foot Protection

To protect feet and legs from falling objects, moving machinery, sharp objects, hot materials, chemicals, or slippery surfaces, employees should wear closed-toed shoes, boots, foot guards, leggings, or safety shoes as appropriate. Safety shoes are designed to protect people from the most common causes of foot injuries---impact, compression, and puncture. Special foot protection is also available for protection against static electricity, sparks, live electricity, corrosive materials, and slipping.

NOTE: Foot protection is particularly important in laboratory, agricultural, and construction work.

IMPORTANT: Do not wear sandals or open-toed shoes in laboratories, shops, or other potentially hazardous areas. Also, avoid the use of mesh shoes if possible.

8. Head Protection

Accidents that cause head injuries are difficult to anticipate or control. If hazards exist that could cause head injury, employees should try to eliminate the hazards, but they should also wear head protection.

Safety hats protect the head from impact, penetration, and electrical shock. Head protection is necessary if you work where there is a risk of injury from moving, falling, or flying objects or if you work near high-voltage equipment. Hard hats should be water resistant, flame resistant, and adjustable. Wear one of the following hard hats as appropriate for your work situation.

- Class A - General service, limited voltage protection
- Class B - Utility service, high-voltage protection
- Class C - Special service, no voltage protection

Follow these guidelines for head safety.

- Check the shell and suspension of your headwear for damage before each use. Look for cracks, dents, gouges, chalky appearance, and torn or broken suspension threads. Discard damaged hats or replace broken parts with replacements from the original manufacturer.
- Discard any hat that has been struck or dropped from a great height, even if there is no apparent damage.
- Do not wear a hard hat backwards, unless this is necessary to accommodate other protective equipment (e.g., welders face shield).
- Do not paint the plastic shell of a hard hat or alter it in any way.

9. Respiratory Protection

WTAMU uses engineering, administrative, and procedural controls to protect people from dangerous atmospheres, including harmful mists, smoke, vapors, and oxygen-deficient atmospheres. When these controls cannot provide adequate protection against harmful atmospheres, respiratory protection is necessary. Contact EHS for respiratory protection equipment training information.

9.1. Usage Requirements

People who use respiratory protection must be physically capable of using and wearing the equipment. In some cases, a physician must determine if an employee is healthy enough to use a respirator. In addition, all people required to wear respirators must be formally trained and instructed in proper equipment usage. This training should include instruction on common respiratory hazards and symptoms of exposure.

9.2. Types of Respirators

It is important to select the right respirator for the job. There are many types of respirators and each type protects against different hazards. Respirators are classified according to these factors.

- Air source: supplied air or ambient air
- Pressure: positive or negative
- Mask configuration

The following lists information on various respirators:

Supply Air Respirators - Self-Contained Breathing Apparatus (SCBAs) use supplied air from a cylinder carried by the user. Airline respirators require a compressor or cylinder(s) and an airline hose to the user. Supply air respirators are necessary in oxygen deficient atmospheres. When using a supply air respirator, have a back-up person with a SCBA standing nearby.

Air-Purifying Respirators - Air purifying respirators use ambient air and cannot be used in oxygen deficient atmospheres, IDLH atmospheres, or areas where the identity or concentration of a contaminant is unknown. Ambient air is purified by a chemical cartridge, canister, or particulate filter. When using air-purifying respirators remember the following.

- Users must select the proper cartridge/canister/filter.
- Cartridges and canisters must be replaced if the user notices an odor, taste, or throat irritation. Wet, damaged, and grossly contaminated cartridges/canisters must also be replaced.
- Powered air-purifying respirators use filtered ambient air in a positive-pressure continuous flow mode.
- Disposable or single-use respirators are made of cloth or paper and are primarily used for nuisance dusts.
- All filters (HEPA, dust pads, and disposable respirators) must be replaced if any of the following conditions occur.
 - Breathing becomes difficult.
 - Filter or dust respirator becomes damaged, visibly dirty, wet, or contaminated on the inside.

Mask Types

- Full-face mask covers the face from the hairline to below the chin. This type of mask provides eye protection.
- Half-face mask covers the face from above the nose to below the chin.

The following table highlights various respirators and their ability to protect against different hazards:

RESPIRATOR TYPE		PROTECTION	NO PROTECTION
Filter Respirator (HEPA cartridge)	Dust Fumes Smoke Mist Microorganisms Asbestos	Chemical vapors or gases Oxygen deficiency	
Chemical Cartridge/Canister Respirators	Certain gases and vapors up to a particular concentration	Oxygen deficiency Particulate matter	
Air Supply Respirator	Depending on type: Particulates Chemical vapors and gases Oxygen deficiency		

NOTE: Only use respirators that are approved by NIOSH/MSHA.

9.3. Selecting a Respirator

When selecting a respirator, consider the following factors.

- Type of hazards.
- Identity and concentration of the contaminant.
- Time constraints.
- Activity of the person wearing the respirator.
- Degree of protection provided by each type of respirator.

Follow these guidelines for selecting the correct respirator.

- Use a HEPA filtered respirator
 - If the contaminant is a biological hazard.

- Use a supply air respirator
 - If the identity and/or concentration of the contaminant is not known.
 - If an oxygen deficient atmosphere is known or suspected.
 - If an IDLH condition exists.
- Use a SCBA instead of an airline respirator
 - If an airline respirator could be damaged by work or conditions within the area.

IMPORTANT: Respirators are available in different sizes. Always fit-test a respirator to select the correct size.

9.4. Using Respirators Safely

Follow these guidelines to ensure safe respirator usage.

- Make sure you have the correct respirator for the job.
- Inspect respirators before each use.
- Shave facial hair and put in dentures (if applicable) to ensure a good seal with the facemask.
- If you are working in a dangerous area, have another person present.

Remember that contaminants can harm the body as well as the respiratory tract; wear protective clothing as appropriate.

Return to fresh air and remove the respirator in the following conditions.

- You feel nauseous, dizzy, or ill.
- You have difficulty breathing.
- The canister, cartridge, or filter needs to be replaced.
- Properly clean and store all reusable respirators.

In addition to the guidelines above, follow these instructions for respirator usage.

- Do not use a respirator unless you have been formally trained and have fit-tested the respirator you plan on using.
- Do not mistakenly use a filter respirator for protection against gases or vapors.
- Never remove a respirator in a contaminated atmosphere.
- Do not talk unnecessarily or chew gum while wearing a respirator.
- Do not wear contact lenses while wearing a respirator.
- Do not allow your hair or eyeglass frames to interfere with the face mask seal.

10. Showers

Emergency safety showers provide emergency treatment for people exposed to harmful materials. If a person is contaminated with harmful chemicals, the emergency shower provides an instant deluge to protect the person from further exposure. WTAMU uses ANSI standards for shower locations, travel distance, testing, and function.

Emergency showers must be located to ensure accessibility within 10 seconds.

Travel distance between a shower and potential hazards may not exceed 100 feet.

IMPORTANT: Emergency showers are for emergencies only. If a chemical spill involving personal exposure occurs, pull the cord and remove affected clothing immediately. Stay in the shower for at least 15 minutes.

11. Training

West Texas A & M University Environmental Health and Safety will follow the Texas A & M University System Policy [33.05.02 Required Employee Training](#). Staff and faculty whose required training is delinquent more than 90 days will have their internet access terminated until all trainings are completed. Only Blackboard and Single Sign-on will be accessible. Internet access will be restored once training has been completed. Student workers whose required training is delinquent more than 90 days will need to be terminated by their manager through Student Employment.

12. Record Retention

No official state records may be destroyed without permission from the Texas State Library as outlined in [Texas Government Code, Section 441.187](#) and [13 Texas Administrative Code, Title 13, Part 1, Chapter 6, Subchapter A, Rule 6.7](#). The Texas State Library certifies Agency retention schedules as a means of granting permission to destroy official state records.

West Texas A & M University Records Retention Schedule is certified by the Texas State Library and Archives Commission. West Texas A & M University Environmental Health and Safety will follow [Texas A & M University Records Retention Schedule](#) as stated in the Standard Operating Procedure [61.99.01.W0.01 Records Management](#). All official state records (paper, microform, electronic, or any other media) must be retained for the minimum period designated.

Related Statutes, Policies, or Requirements

Contact Office

WTAMU Environmental Health and Safety
(806) 651-2270